GSM Voice Recorder

Magnet & SD card & Voice activation

Q815



Feature

- GSM Voice Recorder with micro SD card slot
- HD Recording, file format: 32kbs WAV
- Recording Mode: Voice Activation & Schedule & Remote
- Voice DSP, clear record the voice within five meters
- Support maximum 32G byte SD card
- 5000mAh Lithium-Polymer battery
- Maximum 400 days working time
- Drop-trigger alarm build-in
- Water-Proof design with strong magnets built-in
- Police & Detector's Best Choice

Working Day

| Pacarding mode | | Q8 Serie | s of Model | |
|---|-------------|-------------|-------------|-------------|
| Recording mode | Q805 | Q810 | Q815 | Q820 |
| Keep recording, Never stop | 110 hours | 220 hours | 330 hours | 440 hours |
| Wake up a hour per day, in schedule sleep mode | 100 days | 200 days | 300 days | 400 days |
| Drop Alarm | Yes | Yes | Yes | Yes |
| Battery Capacity | 5000mAh | 10000mAh | 15000mAh | 20000mAh |
| Size | 117x59x30mm | 153x58x34mm | 153x58x39mm | 153x58x45mm |
| Weight | 227g | 369g | 465g | 569g |

Multi-Recording Mode

Voice Activation Recording Mode

When the recorder detects ambient sound, it will automatically start recording

Schedule Recording Mode

According to pre-set schedule, the Recorder automatically start recording

GSM Remote Recording Mode

User remote to start recording by phone call or SMS

Multi-Sleep Mode

Much prolong the recording working time

Voice Activation Sleep Mode

When the recorder detects ambient sound, it will wake up from deep sleep mode then start recording

Schedule Sleep Mode

According to pre-set schedule, the recorder will wake up from deep sleep mode then start recording

Vibration Sleep Mode

When the recorder detects vibration, it will wake up from deep sleep mode then start recording

Remote Control

Playback appointed time from recording file by phone User can send the SMS command to recorder then listen the playback appointed content from SD recording file by phone call

Start or stop recording by Call or SMS

User can remote start or stop recording by SMS command

Real-time monitor the ambient sound by phone

User can call the recorder to listen real-time sound nearby recorder

without SIM card

Recorder works just like a regular recorder even without sim card, user can setup the recording mode by recording button or control file

Smart Fold

the recording file will be auto grouped to the fold which named by date



Drop-trigger alarm

- Drop alert will be automatically activated once tracker is attached on the iron surface.
- Owner will receive a immediate drop alert by call or SMS once device is fell off the iron surface.

IPX7 water-proof

Waterproof 30 mins under 1 meter water



| | | C-R&TTE CE | | | | |
|-----------------------|--|---|----------------------------------|---------|--|--|
| | ate No. | : CTL1312232035-W | | | | |
| Applicant& Address | | VJOY CAR ELECTRONICS LIMITED No.9177, BeiQing Road, XiangHuaQiao Town, QingPu District, | | | | |
| Address | | Shanghai, 201799 China | | | | |
| Manufa | acturer& | | R ELECTRONICS LIMITED | | | |
| | Address Building 20th, Xin Wei First Industry Park, FuYong Street, | | | | | |
| | | ShenZhen, 518100 Chir | na | | | |
| | ption of | : GPS TRACKER | | | | |
| Equipr | | | 1800 MHz, with GPS function | | | |
| Model | Name | | 18, T4400, T8800, T15400, T13, T | F110, | | |
| Trade | | TT220, TT330, TT520 ; VJOY | | | | |
| Trade | Name | : 0301 | | | | |
| Essential R | equirement | Applied Specifications/ Standards | Documentary Evidence | Result | | |
| Art. 3.1(a) | Safety | EN 60950-1:2006+A11:2009+A1:2010+ A12:2011 | Test Report CTL1312232035-WS | Conform | | |
| Art. 3.1(a) | Health | EN 62311: 2008 | Test Report CTL1312232035-WH | Conform | | |
| Art. 3.1(b) EMC | ETSI EN 301 489-1 V1.9.2 | N/29 51 | | | | |
| | EMC | ETSI EN 301 489-3 V1.4.1 | Test Report CTL1312232035-WE | Conform | | |
| | - | ETSI EN 301 489-7 V1.3.1 ETSI EN 300 440-1 V1.6.1 | 201 | | | |
| Art. 3.2 Radio | Radio | ETSI EN 300 440-2 V1.4.1 | Test Report CTL1312232035-WR02 | Conform | | |
| | | ETSI EN 301 511 V9.0.2 | Test Report CTL1312232035-WR01 | Conform | | |
| he EUT de | escribed at | ove has been tested by us with the | | | | |
| with the cou | uncil R&TT | E directive 1999/5/EC. It is possible | to use CE marking to demonstrate | | | |
| | | ne Directive. | | | | |
| The scope of | of evaluation | on relates to the submitted document | its only. | | | |
| | | | | | | |
| - | - | | ** \$* \$\$ | | | |
| (| C | 1 .0 | A Cr. + | | | |
| | - | They Or: | a corona L * | | | |
| | | 12-11 | 2 non 3 | | | |
| C | | | | | | |
| - | | For Chief Executive | - Contraction | | | |

Self-locking sim slot

to make sure sim card works well even at shock or vibration environment





Specification

- Size:153mm x 58mm x 39mm, Weight: 465g
- Build-in micro SD card
- GPRS:MTK 6260D
- Quad band; 850/900/1800/1900 MHz
- Antennae: Internal, GPRS Class 12
- Power:Rechargeable, 15000 mAh, Lithium-Polymer Battery
- Built-in Vibration/motion sensing





